

USB 3.0 3 to 2 4K Docking Station



DU3B00

The USB 3.0 3 to 2 4K Docking Station is designed for extra connectivity demands. With the docking station, you can extend the connection of a computer to more USB peripherals, Ethernet network, the speaker and the microphone through one single USB cable. With the built-in USB 3.0 ports, the docking station enables you to enjoy the super speed data transmission between USB peripherals. Aside from USB 3.0, this product is compliant with USB 2.0/1.1 specification. You will be able to keep and use your USB 2.0/1.1 devices as usual. In addition, the docking station is equipped with video output. With the DVI, HDMI and DP ports, you can mirror your primary screen, or extend the Window desktop allowing visibility of more applications at the same time. Enhanced expansion capability plus the stylish appearance, this docking station with video is the most versatile accessory that also complements your home or office space.

* Incorporates HDMI® technology.

Features

- USB 3.0 downstream port x3
 - Downward compatible with USB 2.0/1.1
 - One USB port supports BC 1.2 charging
- Display Port
 - DP/HDMI: resolution up to 3840x2160 pixels *
 - DVI: resolution up to 2048x1152 pixels
- Support audio 2.1 channel
- Support Gigabit Ethernet

NOTE: Please note that when using the DP (or HDMI) and the DVI connector simultaneously, the DP (or HDMI) connector will not be able to reach 4K resolutions.

System Requirements

- Operating Systems:
 - Microsoft: Windows® 7 SP1 or later/ Windows® 8/ Windows® 8.1/ Windows® 10

Package Content

- USB 3.0 3 to 2 4K Docking Station x1
- USB Cable x1
- Power Adapter x1
- CD (Driver and User's Manual) x1
- Quick Installation Guide x1

Specifications

Connector	Video Output	DP Female Connector HDMI Female Connector * DVI Female Connector
	Host Upstream Link	USB B Type Female Connector
	HUB Downstream Link	USB A Type Female Connector (USB 3.0 x3, with BC1.2 x1)
	Audio Port	3.5mm stereo mini-jack
	Ethernet Port	RJ45 Connector
	Power	DC power jack
Video	Resolution	DP/HDMI: 3840x2160 * DVI: 2048x1152
	Color Depth	16 Bits and 32 Bits
Audio	Channel	2.1 CH
Ethernet	Type	10/100/1000 Base-T
	Power Mode	Self-powered
Power	Power Adapter	Input: AC 100-240V Output: DC 5V/4A
	Housing	PC + ABS (Plastic)
Physical Properties	Dimension	189.1(L) x 74.49(W) x 26.32(H) mm
	Operation Temperature	0~40 degree
Working Environment	Storage Temperature	-20~70 degree
	Compliance	CE, FCC

Application



GOOD WAY TECHNOLOGY CO., LTD.

3F, No.135, Lane 235 Pau Chiao Rd., Hsin Tien, Taipei County, Taiwan
 Tel: 886-2-8919-1200 Fax: 886-2-8919-1220~1
<http://www.goodway.com.tw> E-mail:sales@goodway.com.tw

* The DP and HDMI connectors can only be used one at a time. Slide the lid in front of the two connectors to uncover the connector you want to use and connect it to the monitor. Please note that when using the DP (or HDMI) and the DVI connector simultaneously, the DP (or HDMI) connector will not be able to reach 4K resolutions.